

**NETTOYANT FOUR - DN24A**

**SAFETY DATA SHEET**

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

**SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1. Product identifier**

Product name : NETTOYANT FOUR

Product code : DN24A.

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**1.3. Details of the supplier of the safety data sheet**

Registered company name : FABRICATION CHIMIQUE ARDECHOISE.

Address : 1041, chemin de la Digue du Rhône.07300.TOURNON cedex.FRANCE.

Telephone : 04-75-07-82-10. Fax : 04-75-07-16-89.

menager@fareva.com

<http://www.fareva.com/>

**1.4. Emergency telephone number : +33 (0)1.45.42.59.59.**

Association/Organisation : INRS/ORFILA <http://www.centres-antipoison.net>.

**SECTION 2 : HAZARDS IDENTIFICATION**

**2.1. Classification of the substance or mixture**

**In compliance with EC regulation No. 1272/2008 and its amendments.**

Aerosol, Category 2 (Aerosol 2, H223 - H229).

Skin corrosion, Category 1A (Skin Corr. 1A, H314).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

**2.2. Label elements**

Detergent mixture (see section 15).

Mixture for aerosol application.

**In compliance with EC regulation No. 1272/2008 and its amendments.**

Hazard pictograms :



GHS02



GHS05

Signal Word :

DANGER

Product identifiers :

EC 215-185-5 SODIUM HYDROXIDE

Hazard statements :

H223

Flammable aerosol.

H229

Pressurised container: May burst if heated.

H314

Causes severe skin burns and eye damage.

Precautionary statements - General :

P101

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

Precautionary statements - Prevention :

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**NETTOYANT FOUR - DN24A**

P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary statements - Response :	
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/...
Precautionary statements - Storage :	
P410 + P412	Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122 °F.
Precautionary statements - Disposal :	
P501	Eliminate the contents / container according to the local regulations.

**2.3. Other hazards**

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

**SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**

**3.2. Mixtures**

**Composition :**

Identification	(EC) 1272/2008	Note	%
INDEX: 601_004_00_0 CAS: 106-97-8 EC: 203-448-7 REACH: 01-2119474691-32	GHS02, GHS04 Dgr Flam. Gas 1, H220 Press. Gas, H280	C [1] [7]	2.5 <= x % < 10
<b>BUTANE</b> INDEX: 011_002_00_6 CAS: 1310-73-2 EC: 215-185-5 REACH: 01-2119457892-27	GHS05 Dgr Met. Corr. 1, H290 Skin Corr. 1A, H314 Eye Dam. 1, H318	[1]	2.5 <= x % < 10
<b>SODIUM HYDROXIDE</b> INDEX: 601_003_00_5 CAS: 74-98-6 EC: 200-827-9 REACH: 01-2119486944-21	GHS02, GHS04 Dgr Flam. Gas 1, H220 Press. Gas, H280	[1] [7]	1 <= x % < 2.5
<b>PROPANE</b> INDEX: A137166 CAS: 137-16-6 EC: 205-281-5 REACH: 01-2119527780--39	GHS06, GHS05 Dgr Skin Irrit. 2, H315 Eye Dam. 1, H318 Acute Tox. 2, H330		0 <= x % < 1
<b>SODIUM N-LAUROYLSARCOSINATE</b> INDEX: A110258 CAS: 110-25-8 EC: 203-749-3 REACH: 01-2119488991-20	GHS07, GHS05, GHS09 Dgr Skin Irrit. 2, H315 Eye Dam. 1, H318 Acute Tox. 4, H332	[1]	0 <= x % < 1
<b>(Z)-N-MÉTHYL-N-(1-OXO-9-OCTADECÉNYL)GLYCINE</b>	Aquatic Acute 1, H400 M Acute = 1		

(Full text of H-phrases: see section 16)

**NETTOYANT FOUR - DN24A**

---

**Information on ingredients :**

[7] Propellant gas

[1] Substance for which maximum workplace exposure limits are available.

---

**SECTION 4 : FIRST AID MEASURES**

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

**4.1. Description of first aid measures**

**In the event of splashes or contact with eyes :**

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

**In the event of splashes or contact with skin :**

Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

**In the event of swallowing :**

Do not give the patient anything orally.

Seek medical attention immediately, showing the label.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available.

---

**SECTION 5 : FIREFIGHTING MEASURES**

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

**5.1. Extinguishing media**

Keep packages near the fire cool, to prevent pressurised containers from bursting.

**Suitable methods of extinction**

Prevent the effluent of fire-fighting measures from entering drains or waterways.

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)

- carbon dioxide (CO<sub>2</sub>)

**5.3. Advice for firefighters**

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

---

**SECTION 6 : ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For non first aid worker**

Avoid any contact with the skin and eyes.

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**NETTOYANT FOUR - DN24A**

---

**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Neutralise with an acidic decontaminant.

If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.

Clean preferably with a detergent, do not use solvents.

Use some absorbent.

The elimination must be carried out by a registered salvage professional.

**6.4. Reference to other sections**

No data available.

---

**SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

**7.1. Precautions for safe handling**

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

**Fire prevention :**

Handle in well-ventilated areas.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

**7.2. Conditions for safe storage, including any incompatibilities**

No data available.

**Storage**

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

**Packaging**

Always keep in packaging made of an identical material to the original.

**7.3. Specific end use(s)**

No data available.

**NETTOYANT FOUR - DN24A**

**SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1. Control parameters**

**Occupational exposure limits :**

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	1000 ppm				
1310-73-2			2 mg/m <sup>3</sup>		
74-98-6	1000 ppm				

- Germany - AGW (BAuA - TRGS 900, 08/08/2019) :

CAS	VME :	VME :	Excess	Notes
106-97-8		1000 ppm 2400 mg/m <sup>3</sup>		4(II)
74-98-6		1000 ppm 1800 mg/m <sup>3</sup>		4(II)
110-25-8		0.05 mg/m <sup>3</sup>		2 (II)

- France (INRS - ED984 / 2020-1546) :

CAS	VME-ppm :	VME-mg/m <sup>3</sup> :	VLE-ppm :	VLE-mg/m <sup>3</sup> :	Notes :	TMP No :
106-97-8	800	1900	-	-	-	-
1310-73-2	-	2	-	-	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	600 ppm 1450 mg/m <sup>3</sup>	750 ppm 1810 mg/m <sup>3</sup>		Carc	
1310-73-2		2 mg/m <sup>3</sup>			

**8.2. Exposure controls**

**Personal protection measures, such as personal protective equipment**

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

**- Eye / face protection**

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

**- Hand protection**

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex

- PVC (polyvinyl chloride)

Recommended properties :

- Impervious gloves in accordance with standard EN ISO 374-2

**NETTOYANT FOUR - DN24A**

---

**- Body protection**

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Wear suitable protective clothing, in particular overalls and boots. These items must be kept in good condition and cleaned after use.

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

---

**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

**General information :**

Physical state :

Fluid liquid.

Spray.

**Important health, safety and environmental information**

pH :

Not stated.

Strongly basic.

Boiling point/boiling range :

100 °C.

Flash point interval :

Not relevant.

Vapour pressure (50°C) :

Below 110 kPa (1.10 bar).

Density :

< 1

Water solubility :

Dilutable.

Melting point/melting range :

0 °C.

Self-ignition temperature :

Not specified.

Decomposition point/decomposition range :

Not specified.

Flame height :

>= 4cm.

Flame duration :

2 s <= t < 7 s.

**9.2. Other information**

No data available.

---

**SECTION 10 : STABILITY AND REACTIVITY**

**10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

No data available.

**10.4. Conditions to avoid**

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating

- heat

- frost

#### 10.5. Incompatible materials

#### 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

---

### SECTION 11 : TOXICOLOGICAL INFORMATION

#### 11.1. Information on toxicological effects

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure for up to three minutes.

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

##### 11.1.1. Substances

###### Acute toxicity :

SODIUM N-LAUROYLSARCOSINATE (CAS: 137-16-6)

Inhalation route (Dusts/mist) : 0.25 < LC50 <= 0.5 mg/l  
Species : Rat  
OECD Guideline 403 (Acute Inhalation Toxicity)  
Duration of exposure : 4 h

(Z)-N-MÉTHYL-N-(1-OXO-9-OCTADECÉNYL)GLYCINE (CAS: 110-25-8)

Oral route : LD50 > 2000 mg/kg  
Species : Rat  
OECD Guideline 401 (Acute Oral Toxicity)

Inhalation route (n/a) : LC50 = 1.37 mg/l  
Species : Rat  
Duration of exposure : 4 h

##### 11.1.2. Mixture

###### Skin corrosion/skin irritation :

Corrosive classification is based on an extreme pH value.

###### Serious damage to eyes/eye irritation :

Corrosive classification is based on an extreme pH value.

---

### SECTION 12 : ECOLOGICAL INFORMATION

#### 12.1. Toxicity

##### 12.1.1. Substances

(Z)-N-MÉTHYL-N-(1-OXO-9-OCTADECÉNYL)GLYCINE (CAS: 110-25-8)

Crustacean toxicity : EC50 = 0.68 mg/l  
Factor M = 1  
Species : Daphnia magna  
Duration of exposure : 48 h

##### 12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

#### 12.2. Persistence and degradability

##### 12.2.1. Substances

(Z)-N-MÉTHYL-N-(1-OXO-9-OCTADECÉNYL)GLYCINE (CAS: 110-25-8)

**NETTOYANT FOUR - DN24A**

Biodegradability : Rapidly degradable.

**12.3. Bioaccumulative potential**

No data available.

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Other adverse effects**

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

**SECTION 14 : TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2019 - IMDG 2018 - ICAO/IATA 2020).

**14.1. UN number**

1950

**14.2. UN proper shipping name**

UN1950=AEROSOLS, flammable, corrosive

**14.3. Transport hazard class(es)**

- Classification :



2.1+8

**14.4. Packing group**

-

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5FC	-	2.1+8	-	1 L	190 327 344 625	E0	1	D

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation
	2	See SP63	-	See SP277	F-D, S-U	63 190 277 327 344 381 959	E0	- SW1 SW22	SG69



**NETTOYANT FOUR - DN24A**

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	2.1	8	-	Forbidden	Forbidden	Forbidden	Forbidden	-	-
	2.1	8	-	Forbidden	Forbidden	-	-	-	-

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No data available.

**SECTION 15 : REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**- Classification and labelling information included in section 2:**

The following regulations have been used:

- Directive 75/324/CEE modified by directive 2013/10/UE
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2018/1480 (ATP 13)

**- Container information:**

Packaging to be fitted with child-resistant fastenings (see EC Regulation No. 1272/2008, Annex II, Part 3).

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

**- Particular provisions :**

No data available.

**- Labelling for detergents (EC Regulation No. 648/2004,907/2006) :**

- less than 5 % : anionic surfactants
- less than 5 % : nonionic surfactants
- 5 % or over but less than 15 % : aliphatic hydrocarbons

**15.2. Chemical safety assessment**

No data available.

**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.

**Abbreviations :**

- STEL : Short-term exposure limit
- TWA : Time Weighted Averages
- TMP : French Occupational Illness table
- TLV : Threshold Limit Value (exposure)
- AEV : Average Exposure Value.

**NETTOYANT FOUR - DN24A**

---

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS05 : Corrosion

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.